

Platform

- Self-closing saloon style gates
- Removable platform console box
- Lanyard attach points
- Full proportional drive joystick control with integral thumb steer switch
- Proportional lift/lower speed control
- Joystick enable for lift and drive

Functional Equipment & Accessories

- Pothole protection system
- AC cable to platform
- Battery condition indicator
- Hour meter
- 3 section steel mast
- Manual descent
- Horn
- Non-marking solid tyres (323 x 100)
- Slope alarm and light
- Tie down lugs

Available Options

- All motion alarm
- Descent alarm
- Alarm package ¹
- Amber strobe light
- Plugs & Sockets

Power & Transmission

- 4 x 6V 220 A/hr deep cycle batteries
- Automatic positive traction
- Programmable "Personality" settings
- On-board self-diagnostic testing
- Swing-out battery/electrical compartment doors
- 20 amp automatic battery charger
- Dual motor direct electric front wheel drive & steer
- Dual wheel automatic brakes
- Emergency brake release



JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company



T: 01332 856 359 F: 01332 810 769

E: info@workplatformltd.co.uk W: www.workplatformltd.co.uk

Printed in UK
 FORM No.: DS005-0308-50
 PART NO.: DS005-ENGLISH



1230ES

Working height	5.66 m
A. Platform height – elevated	3.66 m
B. Platform height – lowered	0.52 m
C. Platform rail height	1.10 m
D. Stowed height	1.65 m
E. Platform size (W x L)	0.69 m x 1.26 m
F. Overall length	1.36 m
G. Overall width	0.76 m
H. Wheelbase	1.04 m
I. Ground clearance (stowed)	6.5 cm
Platform capacity ¹	230 kg
Lift/lower time	12 /12 sec.
Maximum drive height	3.66 m
Weight ²	790 kg
Maximum ground bearing pressure	8.65 kg/cm ²
Drive speed lowered	4.8 km/h
Drive speed elevated	0.8 km/h
Gradeability	25%
Turning radius – inside	11 cm
Turning radius – outside	1.46 m
Tyres (non-marking solid)	323 x 100
Brakes	Automatic Spring Applied
Drive	24V Electric 6 kW
Batteries	4 x 6V 220 A/hr
Charger (120/240V – 50/60Hz)	20 Amp Automatic
Hydraulic system	4.0 L

¹Capacity - 1 person + tools and equipment up to maximum 230kg.

²Certain options or country standards may increase weight and/or dimensions.

