

## JLG AM SERIES



- Choice of models with working heights from 6.4 m to 14 m\*
- One person operation and set up
  - On-board battery charger
  - AC power cable to platform
- Attractive optional step-in moulded platform
  - Non-marking tyres for use on indoor floor surfaces

\* Model 15AMI - 6.4 m working height    Model 20AM - 8 m working height  
 Model 25AM - 9.5 m working height    Model 30AM - 11 m working height  
 Model 36AM - 13 m working height    Model 41AM - 14 m working height

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



### Range of Quick change platforms

A family of platforms that can be changed without the need for tools to suit your specific needs.



### Easy to load and transport

A sliding mechanism allows for easy loading. A tilt back system that allows larger models to roll through standard doorways.



### Strong Anodised Mast

A mast that is more rigid for less deflection and sway and guides that need no lubrication.



### Excellent manoeuvrability

The six-wheel design gives enhanced manoeuvrability and large 25 cm wheels provide ease of movement.



### Automatic Battery Charger

A fully automatic charger that determines when to shut off during the charging period.



### Model 15AMI - without outriggers

A push around lift without the need for outriggers. Ideal when working in confined areas.



**workplatform**  
powered access specialists

T: 01332 856 359    F: 01332 810 769  
 E: info@workplatformltd.co.uk    W: www.workplatformltd.co.uk

### JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.  
 Kilmartin Place, Tannochside Park,  
 Uddingston, G71 5PH, Scotland.  
 Tel: 01698 811005  
 Fax: 01698 811055

[www.jlg.com](http://www.jlg.com)



## ACCESSMASTER® PERSONNEL LIFTS

	15AMI	20AM	25AM	30AM	36AM	41AM
Platform Height	4.57 m	6.22 m	7.67 m	9.14 m	11.05 m	12.42 m
Platform Capacity	160 kg	160 kg	160 kg	135 kg	135 kg	135 kg
Overall Height - Stowed	1.97 m	1.97 m	1.97 m	1.97 m	2.64 m	2.64 m
Overall Width - Stowed	0.74 m	0.74 m	0.74 m	0.74 m	0.74 m	0.74 m
Overall Length - Stowed	1.33 m	1.19 m	1.24 m	1.32 m	1.38 m	1.46 m
Overall Length - Without Platform	1.33 m	1.19 m	1.19 m	1.19 m	1.35 m	1.35 m
Overall Height - Tilted Back	—	—	—	—	1.92 m	1.96 m
Overall Length - Tilted Back	—	—	—	—	2.74 m	2.74 m
Ground Entry Height	0.48 m	0.48 m	0.48 m	0.48 m	0.48 m	0.48 m
Outrigger Footprint Length	—	1.73 m	1.73 m	1.88 m	2.13 m	2.13 m
Outrigger Footprint Width	—	1.57 m	1.57 m	1.83 m	2.18 m	2.18 m
Distance to Wall - Front	0.00 m	0.28 m	0.20 m	0.20 m	0.42 m	0.34 m
Distance to Wall - Side	0.04 m	0.44 m	0.44 m	0.60 m	0.75 m	0.75 m
Gross Vehicle Weight - AC *	425 kg	324 kg	363 kg	438 kg	484 kg	530 kg
Gross Vehicle Weight - DC *	450 kg	356 kg	395 kg	470 kg	515 kg	560 kg

