

## P R E L I M I N A R Y   S P E C I F I C A T I O N S

**Standard Features and Available Options  
Liftlux Series Electric Scissor Lifts**

	153-12	180-12
<b>Platform</b>		
1.16 m x 3.91 m platform	●	●
1.49 m single manual roll-out deck extension	●	●
Moveable and removable platform console box	●	●
Lanyard attach points	●	●
Proportional drive control	●	●
<b>Power &amp; Transmission</b>		
8 x 6V 350 A/hr deep cycle batteries	●	●
Removable battery/electrical compartment hoods	●	●
220V 50 amp automatic battery charger	●	●
Dual front wheel drive	●	●
Dual wheel brakes	●	●
Hydraulic transmission	●	●
<b>Functional Equipment &amp; Accessories</b>		
Pothole protection system	—	—
AC cable to platform	○	○
Platform console function status LED's <sup>1</sup>	●	●
Battery condition indicator	●	●
Hour meter	●	●
Fold down/drop down handrails	●	●
Inward swing gate	●	●
Platform work lights	—	—
Full grease lubrication on all scissor arm bushings	●	●
Scissor maintenance prop	●	●
Manual descent	●	●
Horn	●	●
Non-marking solid tyres (630 x 203)	●	●
Variable slope alarm and light	—	—
2 degree tilt alarm and indicator light	—	●
3 degree tilt alarm and indicator light	●	—
All motion alarm	—	—
Travel alarm	●	●
Descent alarm	—	—
Ground control selector switch with key lock	●	●
Lifting lugs	●	●
Tie down lugs	○	○
Flashing amber beacon	●	●
Drive disconnect	●	●



T: 01332 856 359 F: 01332 810 769

E: info@workplatformltd.co.uk W: www.workplatformltd.co.uk

● Standard ○ Option — Not Available

<sup>1</sup> Provides indicator LED lights at platform control console for lift, drive, tilt, hydraulic jacks and overload.