

Platform

- 0.91 m roll-out deck extension
- Fold-down handrails
- Self-closing gate
- Removable platform console box
- Lanyard attach points
- Full proportional drive joystick control with integral thumb steer switch
- Proportional lift/lower speed control
- Joystick enable for lift and drive
- Load sensing system
- Two speed drive selection

Power & Transmission

- Two Wheel Direct Electric Drive
- 8 x 6V 370 A/hr deep cycle batteries
- On-Board diesel powered quick charge gen set
- Automatic traction control
- Programmable "Personality" settings
- On-board self-diagnostic testing
- Detachable battery compartments
- 23 amp automatic battery charger
- Automatic rear wheel brakes
- Sculptured ABS hoods

¹ Includes all-motion alarm and amber strobe light.

Functional Equipment & Accessories

- 3 degree tilt alarm and indicator light
- Steel scissor guards
- 240/55 - 17.5 non marking foam filled tyres
- Oscillating rear axle
- Lifting/tie down lugs
- Lubrication free scissor arm bushings
- Scissor maintenance prop
- AC cable to platform
- Ground control selector switch with key lock
- Battery condition indicator
- Hour meter
- Horn
- Manual descent pull cable

Available Options

- All wheel assist
- Hydraulic levelling jacks
- All motion alarm
- Descent alarm
- Alarm package ¹
- Platform work-lights
- Amber strobe light
- Plugs and Sockets



JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

Printed in UK
 FORM No.: DS067-0208-500
 PART NO.: DS067-ENGLISH



T: 01332 856 359 F: 01332 810 769

E: info@workplatformltd.co.uk W: www.workplatformltd.co.uk



M3369

A. Platform height – elevated	10.06 m
B. Platform height – lowered	1.69 m
C. Platform railing height ¹	1.10 m
D. Stowed height (rails folded)	1.98 m
E. Platform size	1.65 m x 2.92 m
F. Deck extension	0.91 m
G. Overall width ²	1.75 m
H. Overall length ²	3.07 m
I. Wheelbase	2.32 m
J. Ground clearance	0.20 m
Platform capacity	450 kg
Capacity on deck extension	120 kg
Lift/lower time	38/42 sec.
Maximum drive height	10.06 m
Machine weight ^{1 2}	5,250 kg
Maximum ground bearing pressure	8.1 kg/cm ²
Drive speed – lowered	4.8 km/h
Drive speed – elevated	0.8 km/h
Gradeability	35%
Turning radius – inside	2.29 m
Turning radius – outside	4.88 m
Tyres (non-marking)	240/55-17.5
Brakes	Automatic Spring Applied
Drive motors	Dual Electric Traction
Hydraulic pump motor	Perm. Magnet
Batteries	8 x 6V 370 A/hr
Charger (120/240V - 50/60HZ)	23 Amp SCR Automatic
Hydraulic pump	Gear Pump
Hydraulic system	32 L
Generator set	Kubota OC60 Air-cooled 5 kW
Generator fuel tank	15 L

¹ Certain weight and dimensions may vary due to options and to compliance with country standards.

² Dimensions with optional levelling jacks are; Length 3.73 m, Width 1.75 m, Weight +400kg.

Certain options or country standards may increase weight and/or dimensions.

